




F&amp;R



| Model                    | EIW2000                  | EIW3000   | EIW4000 | EIW5000 |
|--------------------------|--------------------------|-----------|---------|---------|
| Proof pressure(MPa)      | 1.5                      |           |         |         |
| Max. working pressure    | 1.0                      |           |         |         |
| Working temperature(°C)  | 5~60                     |           |         |         |
| Filter precision         | 25µm( 5 µm is optional ) |           |         |         |
| Bowl material            | Polycarbonate            |           |         |         |
| Bowl guard (MPa)         | None                     | Available |         |         |
| Pressure adjusting range | 0.15~0.85                |           |         |         |
| Valve type               | With overflow            |           |         |         |

| Model      | Specifications      |               | Drain function                   | Auto drain model |
|------------|---------------------|---------------|----------------------------------|------------------|
|            | *Rated flow (L/min) | *Port size(G) |                                  |                  |
| EIW2000-01 | 1078                | 1/8           | Manual drain                     | EIW2000-01D      |
| EIW2000-02 | 1165                | 1/4           |                                  | EIW2000-02D      |
| EIW3000-02 | 1998                | 1/4           | Zero pressure drain/Manual drain | EIW3000-02D      |
| EIW3000-03 | 2177                | 3/8           |                                  | EIW3000-03D      |
| EIW4000-03 | 5108                | 3/8           |                                  | EIW4000-03D      |
| EIW4000-04 | 5211                | 1/2           |                                  | EIW4000-04D      |
| EIW5000-06 | 6200                | 3/4           |                                  | EIW5000-06D      |
| EIW5000-10 | 6400                | 1             |                                  | EIW5000-10D      |

\* NPT,PT port size is optional

**EIW2000**

Dimensions (mm): 55, 33.5, 15, 15.4, 5.4, 70.5, 168.5, 205.5, 40, 57.5, 40, 2, Bracket, G1/8(G1/4), Pressure Gauge, IN, OUT, With auto drain, Panel Cut Hole,  $\phi 33.5$ .

**EIW3000-EIW4000**

Dimensions (mm): L, G, K, J, C, B, A, E, D, F, M, H, P, 116, 70, 54, 15.4, 8.5, 338, 94, 90, 49.2, 2.3, Bracket, G1, Pressure Gauge, IN, OUT, With auto drain B1, Port size, Panel Cut Hole,  $\phi 52$ .

**EIW5000**

Dimensions (mm): 70, 54, 15.4, 8.5, 116, 338, 94, 90, 49.2, 2.3, Bracket, G1, Pressure Gauge, IN, OUT, With auto drain, Panel Cut Hole,  $\phi 52$ .

| Model   | Port Size (G) | A  | B     | B1    | C     | D  | E    | F    | G    | H    | J   | K    | L  | M | N  | P  |
|---------|---------------|----|-------|-------|-------|----|------|------|------|------|-----|------|----|---|----|----|
| EIW2000 | 1/8"–1/4"     | 40 | 168.5 | 205.5 | 78.5  | 40 | 27   | 30.5 | 33.5 | 49.5 | 5.4 | 15   | 55 | 2 | 33 | 40 |
| EIW3000 | 1/4"–3/8"     | 53 | 210.5 | 224.5 | 92    | 53 | 31.5 | 39   | 40   | 45.5 | 6.5 | 8    | 53 | 2 | 42 | 63 |
| EIW4000 | 3/8"–1/2"     | 70 | 264   | 267   | 113.5 | 70 | 40   | 48   | 53.5 | 54.5 | 8.5 | 10.5 | 70 | 2 | 52 | 73 |
| EIW5000 | 3/4"–1"       | 90 | 343   | 348   | 116.5 | 90 | 47   | 48   | 53.5 | 62   | 8.5 | 10.5 | 70 | 2 | 52 | 84 |