

Specifications

Model	
Port Size	DN10-DN50
Thread	RC3/8"-RC2-1/2"
Body Material	SS316/SS304
Actuator Material	SS304/Aluminum
Seat Seal	PTFE/FPM
Stem seal	PTFE/FPM
Piston seal	FPM/NBR

Model	
Applicable medium	water, neutral gas or liquid, ethanol, oil, organic solvent, steam, alkaline and weak acid solution
Temperature of medium(°C)	PTFE:-10~+200 FPM:-10~+100
Viscosity(mm²/s)	max6020
Installation	any position
Controlling medium	air/neutral gas
Controlling pressure(Bar)	3-8

Post Size	Actuator	Orifice mm	Kv Value	Temperature /Pressure
3/8"	40	10.5	3.7	-10°C~200°C / 0-16Bar
3/8"	50	10.5	3.7	
1/2"	40	13	4.2	
1/2"	50	13	4.2	
3/4"	40	17	8.0	
3/4"	50	17	8.0	
1"	40	24	19	

Post Size	Actuator	Orifice mm	Kv Value	Temperature /Pressure
1"	50	24	19	-10°C~200°C / 0-16Bar
1"	63	24	19	
1-1/4"	63	30	27	
1-1/4"	80	30	27	
1-1/4"	100	30	27	
1-1/2"	63	35	42	
1-1/2"	80	35	42	

Post Size	Actuator	Orifice mm	Kv Value	Temperature /Pressure
1-1/2"	100	35	42	-10°C~200°C / 0-16Bar
2"	63	45	55	
2"	80	45	55	
2"	100	45	55	

Armature+Connector+Timer



Model:
4V110A



Model:
4V220A



Model:
We can produce many Special products based On clients' requirement



Model:
Q22XD-1.2A



Model:
K23D-1.2A



Model:
K23D-2A



Model:
43650C
Connector



Model:
43650B
Connector



Model:
43650A
Connector



Model:
EMCC
Connector



Model:
PUT
Timer



Model:
110PH