







Straight



Metric thread type

Release-ring dimension



ØD: 3, 4, 6, 1/8, 5/32, 1/4 ØD: 1.8, 2

Unit : mm

Model code	Tube O.D. øD	R	A	B	L	Tube end C	Hex. H	X (øX)	Y	Effective area (mm²)	Weight (g)	CAD file name		
PC180-M3M④	1.8	M3×0.5	2.5 [2.2]	12.1	9.6 [9.9]	8.4	5	4.8	—	0.7	1	PC180-M3M		
PC180-M5M④		M5×0.8	3 [3.2]	11.8	8.8 [8.6]		7			0.8	2.3	PC180-M5M		
PC3-M3M④	3	M3×0.5	2.5 [2.2]	13.1	10.6 [10.9]	9.4	5.5	7	6	0.7	1.1	PC3-M3M		
PC3-M5M④		M5×0.8	3 [3.2]	15.6	12.6 [12.4]	10.9	8	9.8	7.8	3	3.4	PC3-M5M		
PC3-M6M④		M6×1	3.9	16.6	12.7					3.7	3.7	PC3-M6M		
PC3-01M④		R1/8	8	15.6	11.6					10	2.9	6.7	PC3-01M	
PC4-M3M④	4	M3×0.5	2.5 [2.2]	15.1	12.6 [12.9]	10.9	8	9.8	7.8	0.9	2.4	PC4-M3M		
PC4-M5M④		M5×0.8	3 [3.2]	15.6	12.6 [12.4]					3.8	3.2	PC4-M5M		
PC4-M6M④		M6×1	3.9	16.6	12.7		6.3			3.6	PC4-M6M			
PC4-01M④		R1/8	8	15.6	11.6		10			6.4	6.6	PC4-01M		
PC4-02M④		R1/4	11	17.3	11.3		14			6.1	14	PC4-02M		
PC6-M5M④	6	M5×0.8	3 [3.2]	17	14 [13.8]	11.7	10	11.8	9.8	3.6	4.5	PC6-M5M		
PC6-M6M④		M6×1	3.9	18	14.1					6.3	4.8	PC6-M6M		
PC6-01M④		R1/8	8	17.6	13.6		6			6	PC6-01M			
PC6-02M④		R1/4	11		11.6		10.6			13	PC6-02M			
PC6-03M④		R3/8	12	19.6	13.3		17			10.6	26	PC6-03M		
PC1/8-M3M④	1/8	M3×0.5	2.5 [2.2]	15.1	12.6 [12.9]	10.9	8	9.8	7.8	0.9	2.5	PC1_8-M3M		
PC1/8-M5M④		M5×0.8	3 [3.2]	15.6	12.6 [12.4]					2.6	3.5	PC1_8-M5M		
PC1/8-M6M④		M6×1	3.9	16.6	12.7		2.9			3.6	PC1_8-M6M			
PC1/8-01M④		R1/8	8	15.6	11.6		10			2.7	6.6	PC1_8-01M		
PC5/32-M3M④	5/32	M3×0.5	2.5 [2.2]	15.1	12.6 [12.9]	10.9	8	9.8	7.8	0.9	2.4	PC5_32-M3M		
PC5/32-M5M④		M5×0.8	3 [3.2]	15.6	12.6 [12.4]					3.8	3.2	PC5_32-M5M		
PC5/32-M6M④		M6×1	3.9	16.6	12.7		3.9			3.6	PC5_32-M6M			
PC5/32-01M④		R1/8	8	15.6	11.6		10			4.3	6.6	PC5_32-01M		
PC5/32-02M④		R1/4	11	17.3	11.3		14			6.1	15	PC5_32-02M		
PC1/4-M5M④	1/4	M5×0.8	3 [3.2]	16.8	13.8 [13.6]	11.4	10	11.8	9.8	3.6	4.2	PC1_4-M5M		
PC1/4-M6M④		M6×1	3.9 [4]	17.8	13.9 [13.8]					5.7	4.6	PC1_4-M6M		
PC1/4-M7M④		M7×1	Ask us for the dimensions											
PC1/4-01M④		R1/8	8	18.4	14.4	11.4	10			11.8	9.8	14.1	6	PC1_4-01M
PC1/4-02M④		R1/4	11	17.8	11.9		14						13	PC1_4-02M
PC1/4-03M④		R3/8	12	19.9	13.6		17						26	PC1_4-03M
PC2-M3M④	2	M3×0.5	2.5 [2.2]	12.1	9.6 [9.9]	8.4	5	4.8	—	0.7	0.9	PC2-M3M		
PC2-M5M④		M5×0.8	3 [3.2]	11.8	8.8 [8.6]		7			1	2.2	PC2-M5M		
PC2-01M④		R1/8	8	15.4	11.4		10			7.4	PC2-01M			
PC180-01M④	1.8	R1/8	8	15.4	11.4	8.4	10	4.8	—	1	7.4	PC180-01M		

※ 1. ④ in Model code / Replaced with "W" for Light-gray color and/or "C" for Clean-room package

※ 2. "L" is a reference value for height dimension after tightening taper thread.

※ 3. Dimensions in [] are for clean-room package products