




PC
Mini

Straight

RoHS compliant



Metric thread type

Release-ring dimension
øD: 3, 4, 6, 1/8, 5/32 øD: 1.8

Unit : mm

Model code	Tube O.D. øD	R	A	B	L	Tube end C	Hex. H	X (øX)	Y	Effective area (mm ²)	Weight (g)	CAD file name		
PC180-M3M④⑤	1.8	M3×0.5	2.5 [2.2]	12.1	9.6 [9.9]	8.4	5	4.8	—	0.7	1	PC180-M3M(※5)		
PC180-M5M④⑤		M5×0.8	3 [3.2]	11.8	8.8 [8.6]		7			0.8	2.3	PC180-M5M(※5)		
PC3-M3M④⑤	3	M3×0.5	2.5 [2.2]	13.1	10.6 [10.9]	9.4	5.5	7	6	0.7	1.1	PC3-M3M(※5)		
PC3-M5M④⑤		M5×0.8	3 [3.2]	15.6	12.6 [12.4]	10.9	8	9.8	7.8	3	3.4	PC3-M5M(※5)		
PC3-M6M④⑤		M6×1	3.9	16.6	12.7							3.7	PC3-M6M	
PC3-01M④⑤		R1/8	8	15.6	11.6		10					2.9	6.7	PC3-01M
PC4-M3M④⑤	4	M3×0.5	2.5 [2.2]	15.1	12.6 [12.9]	10.9	8	9.8	7.8	0.9	2.4	PC4-M3M(※5)		
PC4-M5M④⑤		M5×0.8	3 [3.2]	15.6	12.6 [12.4]							3.8	3.2	PC4-M5M(※5)
PC4-M6M④⑤		M6×1	3.9	16.6	12.7							6.3	3.6	PC4-M6M
PC4-01M④⑤		R1/8	8	15.6	11.6		10				6.4	6.6	PC4-01M	
PC4-02M④⑤		R1/4	11	17.3	11.3		14				6.1	14	PC4-02M	
PC6-M5M④⑤	6	M5×0.8	3 [3.2]	17	14 [13.8]	11.7	10	11.8	9.8	3.6	4.5	PC6-M5M(※5)		
PC6-M6M④⑤		M6×1	3.9	18	14.1					6.3	4.8	PC6-M6M		
PC6-01M④⑤		R1/8	8	17.6	13.6						6	PC6-01M		
PC6-02M④⑤		R1/4	11		11.6		14			13	PC6-02M			
PC6-03M④⑤		R3/8	12	19.6	13.3		17			10.6	26	PC6-03M		
PC1/8-M3M④⑤	1/8	M3×0.5	2.5 [2.2]	15.1	12.6 [12.9]	10.9	8	9.8	7.8	0.9	2.5	PC1/8-M3M(※5)		
PC1/8-M5M④⑤		M5×0.8	3 [3.2]	15.6	12.6 [12.4]						2.6	3.5	PC1/8-M5M(※5)	
PC1/8-M6M④⑤		M6×1	3.9	16.6	12.7						2.9	3.6	PC1/8-M6M	
PC1/8-01M④⑤		R1/8	8	15.6	11.6		10			2.7	6.6	PC1/8-01M		
PC5/32-M3M④⑤	5/32	M3×0.5	2.5 [2.2]	15.1	12.6 [12.9]	10.9	8	9.8	7.8	0.9	2.4	PC5/32-M3M(※5)		
PC5/32-M5M④⑤		M5×0.8	3 [3.2]	15.6	12.6 [12.4]						3.8	3.2	PC5/32-M5M(※5)	
PC5/32-M6M④⑤		M6×1	3.9	16.6	12.7						3.9	3.6	PC5/32-M6M	
PC5/32-01M④⑤		R1/8	8	15.6	11.6		10			4.3	6.6	PC5/32-01M		
PC5/32-02M④⑤		R1/4	11	17.3	11.3		14			6.1	15	PC5/32-02M		

※ 1. ④ in Model code / Replaced with "W" for Light-gray color

※ 2. ⑤ in Model code / Replaced with "C" for Clean-room package

※ 3. "L" is a reference value for height dimension after tightening taper thread.

※ 4. Dimensions in [] are for clean-room package products

※ 5. Visit PISCO website for CAD data of clean-room package products.