






Inner Hex. Straight

RoHS compliant



Metric thread type



Release-ring dimension
ØD: 3, 4, 6, 1/8, 5/32 ØD: 1.8

Unit : mm


Model code	Tube O.D. øD	R	A	B	L	Tube end C	Hex. H	øP	X (øX)	Y	Effective area (mm ²)	Weight (g)	CAD file name
POC180-M3M(4)(5)	1.8	M3 × 0.5	2.5 [2.2]	12.1	9.6 [9.9]	8.4	1.3	5	4.8	—	0.7	0.9	POC180-M3M(4)(5)
POC3-M3M(4)(5)	3	M3 × 0.5	2.5 [2.2]	15.1	12.6 [12.9]	10.9	1.5	8	9.8	7.8	1.9	2.3	POC3-M3M(4)(5)
POC3-M5M(4)(5)		M5 × 0.8	3 [3.2]	15.6	12.6 [12.4]		2				2.8	3.2	POC3-M5M(4)(5)
POC3-M6M(4)(5)		M6 × 1	3.9	18.2	14.3	12.5					3	3.5	POC3-M6M(4)(5)
POC4-M3M(4)(5)	4	M3 × 0.5	2.5 [2.2]	15.1	12.6 [12.9]	10.9	1.5	8	9.8	7.8	1.8	2.2	POC4-M3M(4)(5)
POC4-M5M(4)(5)		M5 × 0.8	3 [3.2]	15.6	12.6 [12.4]		2.5				5.1	3	POC4-M5M(4)(5)
POC4-M6M(4)(5)		M6 × 1	3.9	16.6	12.7		3				7	3.3	POC4-M6M(4)(5)
POC4-01M(4)(5)		R1/8	8	15.8	11.8		3	10			7.4	6.2	POC4-01M(4)(5)
POC6-M5M(4)(5)	6	M5 × 0.8	3 [3.2]	17.5	14.5 [14.3]	11.7	2.5	9.8	11.8	9.8	5.2	4.4	POC6-M5M(4)(5)
POC6-M6M(4)(5)		M6 × 1	3.9	18	14.1		3				7.1	4.7	POC6-M6M(4)(5)
POC6-01M(4)(5)		R1/8	8	17.9	13.9		4				10	13	5.6
POC1/8-M3M(4)(5)	1/8	M3 × 0.5	2.5 [2.2]	15.1	12.6 [12.9]	10.9	1.5	8	9.8	7.8	1.8	2.3	POC1/8-M3M(4)(5)
POC1/8-M5M(4)(5)		M5 × 0.8	3 [3.2]	15.6	12.6 [12.4]		2				3.3	3	POC1/8-M5M(4)(5)
POC1/8-M6M(4)(5)		M6 × 1	3.9	16.6	12.7						3.1	3.6	POC1/8-M6M(4)(5)
POC5/32-M3M(4)(5)	5/32	M3 × 0.5	2.5 [2.2]	15.1	12.6 [12.9]	10.9	1.5	8	9.8	7.8	1.8	2.2	POC5/32-M3M(4)(5)
POC5/32-M5M(4)(5)		M5 × 0.8	3 [3.2]	15.6	12.6 [12.4]		2.5				5.1	3	POC5/32-M5M(4)(5)
POC5/32-M6M(4)(5)		M6 × 1	3.9	16.6	12.7		3				7	3.3	POC5/32-M6M(4)(5)
POC5/32-01M(4)(5)		R1/8	8	15.8	11.8		3	10			7.4	6.2	POC5/32-01M(4)(5)
POC1/4-M5M(4)(5)	1/4	M5 × 0.8	3 [3.2]	17.1	14.1 [13.9]	11.4	2.5	9.8	11.8	9.8	4.8	3.8	POC1/4-M5M(4)(5)
POC1/4-M6M(4)(5)		M6 × 1	4	17.7	13.7		3				7.3	4.1	POC1/4-M6M(4)(5)

- ※ 1. ④ in Model code / Replaced with "W" for Light-gray color
- ※ 2. ⑤ in Model code / Replaced with "C" for Clean-room package
- ※ 3. "L" is a reference value for height dimension after tightening taper thread.
- ※ 4. Dimensions in [] are for clean-room package products
- ※ 5. Visit PISCO website for CAD data of clean-room package products.




Cartridge

RoHS compliant



Release-ring dimension



Unit : mm

Model code	Tube O.D. ØD	R	A	B	L	Tube end C	Hex. H	ØP	X	Y	Effective area (mm ²)	Weight (g)	CAD file name
PCC3-M6M(4)(5)	3	M6 × 0.75	3	14	11	10.9	2	8	9.8	7.8	2.9	2.7	PCC3-M6M(4)(5)
PCC4-M6M(4)(5)	4	M6 × 0.75	3	14	11	10.9	2.5	8	9.8	7.8	5.1	2.6	PCC4-M6M(4)(5)
PCC4-M8M(4)(5)		M8 × 0.75	3.4		10.6		3				7.3	4.9	PCC4-M8M(4)(5)
PCC6-M8M(4)(5)	6	M8 × 0.75	3.4	14.8	11.4	11.7	4	10	11.8	9.8	12.8	3.6	PCC6-M8M(4)(5)
PCC1/8-M6M(4)(5)	1/8	M6 × 0.75	3	14	11	10.9	2	8	9.8	7.8	3	2.7	PCC1/8-M6M(4)(5)

- ※ 1. ④ in Model code / Replaced with "W" for Light-gray color
- ※ 2. ⑤ in Model code / Replaced with "C" for Clean-room package



Page for special specifications



3D CAD data is available at PISCO website.



CAD data is available at PISCO website.