




PU

Union Straight

RoHS compliant



OP.
P.754

3D
CAD

CAD


Unit : mm

Model code	Tube O.D. øD	B	øP	Tube end C	Orifice bore (ømm)	Weight (g)	CAD file name
PU4 ④	4	30.8	10	14.9	2.8	4.7	PU4
PU6 ④	6	34.9	12.5	17	4.3	6.5	PU6
PU8 ④	8	37.8	14.5	18.1	7	9.4	PU8
PU10 ④	10	41.4	17.5	20.2	9	16	PU10
PU12 ④	12	47.8	21	23.4	11	22	PU12
PU16 ④	16	49.4	25	24.1	13	26	PU16
PU5/32 ④	5/32	30.8	10	14.9	2.8	4.7	PU5_32
PU3/16 ④	3/16	35.7	12.5	17.4	3.3	6.7	PU3_16
PU1/4 ④	1/4	34.9	12.5	17	5	6.4	PU1_4
PU5/16 ④	5/16	37.8	14.5	18.1	7	9.4	PU5_16
PU3/8 ④	3/8	41.4	17.5	20.2	9	16	PU3_8
PU1/2 ④	1/2	48.4	21	23.7	11	21	PU1_2
PU5/8 ④	5/8	49.4	25	24.1	13	26	PU5_8

PG

Unequal Union Straight

RoHS compliant



OP.
P.754

3D
CAD

CAD

Unit : mm

Model code	Tube O.D. øD1	Tube O.D. øD2	B	øP1	øP2	Tube end C1	Tube end C2	Orifice bore (ømm)	Weight (g)	CAD file name	
PG6-4 ④	6	4	34.4	12.5	12.5	17	14.9	2.8	6.4	PG6-4	
PG8-4 ④	8	4	36.6	14.5	10.7	18.1	14.9	2.8	7.2	PG8-4	
PG8-6 ④		6	37.9		14.5		17	4.3	8.8	PG8-6	
PG10-6 ④	10	6	39.8	17.5	13	20.2	17	4.3	12	PG10-6	
PG10-8 ④		8	41.1		17.5		18.1	6.5	14	PG10-8	
PG12-8 ④	12	8	44	21	14.5	23.4	18.1	6.2	16	PG12-8	
PG12-10 ④		10	47.6		21		20.2	9	21	PG12-10	
PG12-3/8 ④		3/8	47.6							PG12-3_8	
PG16-10 ④	16	10	52.1	25	25	24.1	20.7	8.4	35	PG16-10	
PG16-12 ④		12	49.5				23.4	10	27	PG16-12	
PG3/16-5/32 ④	3/16	5/32	34.8	12.5	12.5	17.4	14.9	2.8	6.4	PG3_16-5_32	
PG1/4-5/32 ④	1/4	5/32	34.4	12.5	12.5	17	14.9	2.8	6.3	PG1_4-5_32	
PG1/4-4 ④		4								PG1_4-4	
PG1/4-3/16 ④	5/16	3/16	35.3	14.5	14.5	18.1	17.4	3.3	6.5	PG1_4-3_16	
PG5/16-3/16 ④		3/16	38.3				17.4	3.3	8.8	PG5_16-3_16	
PG5/16-1/4 ④		1/4	37.9				17	5	8.7	PG5_16-1_4	
PG3/8-1/4 ④	3/8	1/4	39.8	17.5	13	20.2	17	4.3	12	PG3_8-1_4	
PG3/8-5/16 ④		5/16	41.1		17.5		18.1	6.5	15	PG3_8-5_16	
PG1/2-1/4 ④	1/2	1/4	44.4	21	14.5	23.7	17	4.3	15	PG1_2-1_4	
PG1/2-5/16 ④		5/16	44.3				18.1	6.2	16	PG1_2-5_16	
PG1/2-3/8 ④		3/8	47.9				20.2	9	21	PG1_2-3_8	
PG5/8-1/2 ④	5/8	1/2	49.8	25	25	24.1	23.7	10.7	26	PG5_8-1_2	

Common caution in this page

※ 1. ④ in Model code / Replaced with "W" for Light-gray color, "-C" for Clean-room package, "W-C" for Light-gray color and Clean-room package, "-UC" for Clean-wash and Clean-room package

※ 2. Orifice bore is the smallest passage converted in terms of the diameter.

OP.
P.000

Page for special specifications

3D
CAD

3D CAD data is available at PISCO website.

CAD

CAD data is available at PISCO website.