



PGJ Unequal Plug-in Straight

RoHS compliant

OP.
P.754

3D
CAD

CAD



PGJ4-6, PGJ6-8
PGJ8-10, PGJ10-12

Unit : mm

Model code	Tube O.D. øD1	Tube dia. øD2	B	E	øP	Tube end C	Orifice bore (ømm)	Weight (g)	CAD file name
PGJ4-6④	6	4	38.8	18.9	12.5	17	2.5	3.5	PGJ4-6
PGJ6-4④	4	6	37.7	22.3	10	14.9	2.8	2.9	PGJ6-4
PGJ6-8④	8		43.2	21.9	14.5	18.1	4	5.3	PGJ6-8
PGJ8-4④	4	8	40.2	23.3	12.5	14.9	2.8	3.8	PGJ8-4
PGJ8-6④	6		40.8			17	4.3	4	PGJ8-6
PGJ8-10④	10		46.5	22.9	17.5	20.2	6	8.7	PGJ8-10
PGJ8-1/4④	1/4		40.8	23.3	12.5	17	4.8	4	PGJ8-1_4
PGJ10-4④	4	10	42.2	28.3	12.5	14.9	2.8	4.3	PGJ10-4
PGJ10-6④	6		43.8			17	4.3	4.5	PGJ10-6
PGJ10-8④	8		43.7	24.8	14.5	18.1	6.1	5.8	PGJ10-8
PGJ10-12④	12		51.2	23.5	21	23.4	7.5	13	PGJ10-12
PGJ10-1/4④	1/4		43.8	28.3	12.5	17	4.8	4.5	PGJ10-1_4
PGJ10-5/16④	5/16		43.7	24.8	14.5	18.1	6.1	5.8	PGJ10-5_16
PGJ12-6④	6	12	48.8	33.5	14.5	17	4.3	6	PGJ12-6
PGJ12-8④	8		49.7			18.1	6.1	6.7	PGJ12-8
PGJ12-10④	10		50	28.8	17.5	20.2	8.1	9.6	PGJ12-10
PGJ12-1/4④	1/4		48.8	33.5	14.5	17	4.8	5.9	PGJ12-1_4
PGJ12-5/16④	5/16		49.7			18.1	6.1	6.7	PGJ12-5_16
PGJ12-3/8④	3/8		50	28.8	17.5	20.2	8.1	9.7	PGJ12-3_8
PGJ16-10④	10	16	55.2	30.8	21	20.2	8.1	15	PGJ16-10
PGJ16-12④	12		55.4			23.4	10	16	PGJ16-12
PGJ1/4-5/32④	5/32	1/4	37.7	22.3	10	14.9	2.8	3	PGJ1_4-5_32
PGJ5/16-5/32④	5/32	5/16	40.2	23.3	12.5	14.9	2.8	3.8	PGJ5_16-5_32
PGJ5/16-1/4④	1/4		40.8			17	4.8	4	PGJ5_16-1_4
PGJ3/8-1/4④	1/4	3/8	43.8	28.3	12.5	17	4.8	4.3	PGJ3_8-1_4
PGJ3/8-5/16④	5/16		43.7	24.8	14.5	18.1	6.1	5.6	PGJ3_8-5_16
PGJ1/2-1/4④	1/4	1/2	48.8	33.5	14.5	17	4.8	6.5	PGJ1_2-1_4
PGJ1/2-5/16④	5/16		49.7			18.1	6.1	7.3	PGJ1_2-5_16
PGJ1/2-3/8④	3/8		50	28.8	17.5	20.2	8.1	11	PGJ1_2-3_8

※ 1. ④ in Model code / Replaced with "W" for Light-gray color, "-C" for Clean-room package, "W-C" for Light-gray color and Clean-room package, "-UC" for Clean-wash and Clean-room package

※ 2. Orifice bore is the smallest passage converted in terms of the diameter.