


PKVG Unequal Twin Triple Tee

RoHS compliant




Unit : mm

Model code	Tube O.D. øD1	Tube O.D. øD2	L	E	J	øP1	øP2	Tube end C1	Tube end C2	F1	F2	T	Orifice bore (ømm)	Weight (g)	CAD file name
PKVG8-4 ④	8	4	34.7	20.7	12	15	13	18.1	14.9	40.2	9	15	3	31	PKVG8-4
PKVG8-6 ④		6		21.3									4.6	32	PKVG8-6
PKVG10-6 ④	10	6	40	23.8	14	17.5	15	20.2	17	46.2	10.5	17.5	4.6	44	PKVG10-6
PKVG10-8 ④		8		23.7									7	48	PKVG10-8
PKVG5/16-5/32 ④	5/16	5/32	34.7	20.7	12	15	13	18.1	14.9	40.2	9	15	3	31	PKVG5_16-5_32
PKVG5/16-3/16 ④		3/16		21.7									4	33	PKVG5_16-3_16
PKVG5/16-1/4 ④		1/4		21.3									4.6	31	PKVG5_16-1_4
PKVG3/8-3/16 ④	3/8	3/16	40	24.2	14	17.5	15	20.2	17.4	46.2	10.5	17.5	4	45	PKVG3_8-3_16
PKVG3/8-1/4 ④		1/4		23.8									4.6	43	PKVG3_8-1_4
PKVG3/8-5/16 ④		5/16		23.7									7	47	PKVG3_8-5_16

PZA Union Cross

RoHS compliant



Unit : mm

Model code	Tube O.D. øD	E	øP	Tube end C	F1	F2	ød	T	Orifice bore (ømm)	Weight (g)	CAD file name
PZA8 ④	8	23.2	15	18.2	18	9	3.2	15	7	20	PZA8
PZA10 ④	10	27	17.5	20.7	22.5	11.3	4.2	17.5	9	32	PZA10
PZA12 ④	12	30.7	21	23.4	24.5	12.3	4.2	21	11	46	PZA12
PZA1/4 ④	1/4	20.95	13	17	18	9	3.2	13	5	14	PZA1_4
PZA5/16 ④	5/16	23.2	15	18.2	18	9	3.2	15	7	20	PZA5_16
PZA3/8 ④	3/8	27	17.5	20.7	22.5	11.3	4.2	17.5	9	33	PZA3_8
PZA1/2 ④	1/2	31	21	23.7	24.5	12.3	4.2	21	11	44	PZA1_2

Common caution in this page

- ※ 1. ④ in Model code / Replaced with "W" for Light-gray color, "-C" for Clean-room package, "W-C" for Light-gray color and Clean-room package, "-UC" for Clean-wash and Clean-room package
- ※ 2. Orifice bore is the smallest passage converted in terms of the diameter.