


PLF Female Elbow

RoHS compliant



Unit : mm

Model code	Tube O.D. øD	Rc	A	B	L	øP	Tube end C	E	Hex. H	Orifice bore (ømm)	Weight (g)	CAD file name
PLF4-M5 ④	4	M5 × 0.8	5	19	14	10	14.9	18.7	10	2.8	6.9	PLF4-M5_
PLF4-M6 ④		M6 × 1							14		6.4	PLF4-M6_
PLF4-01 ④		Rc1/8	7	25	20			20.7	17		14	PLF4-01_
PLF4-02 ④		Rc1/4	9.5	31	26						21	PLF4-02_
PLF6-M5 ④	6	M5 × 0.8	5	20.8	14.5	12.5	17	20.3	10	4.1	7.8	PLF6-M5_
PLF6-M6 ④		M6 × 1							14		7.3	PLF6-M6_
PLF6-01 ④		Rc1/8	7	26.8	20.5			21.8	17	4.3	15	PLF6-01_
PLF6-02 ④		Rc1/4	9.5	31.3	25			23.8	21		21	PLF6-02_
PLF6-03 ④		Rc3/8	10.5	33.8	27.5						32	PLF6-03_
PLF8-01 ④	8	Rc1/8	7	28.3	21	14.5	18.1	22.7	14	6.7	16	PLF8-01_
PLF8-02 ④		Rc1/4	9.5	32.3	25			23.7	17		23	PLF8-02_
PLF8-03 ④		Rc3/8	10.5	34.3	27			24.7	21		33	PLF8-03_
PLF10-02 ④	10	Rc1/4	9.5	34.3	25.5	17.5	20.2	26	17	8.3	26	PLF10-02_
PLF10-03 ④		Rc3/8	10.5	36.8	28			27	21		36	PLF10-03_
PLF10-04 ④		Rc1/2	13	40.3	31.5			27.5	24		46	PLF10-04_
PLF12-02 ④	12	Rc1/4	9.5	38	27.5	21	23.4	29.7	17	10.0	31	PLF12-02_
PLF12-03 ④		Rc3/8	10.5	39	28.5				21		40	PLF12-03_
PLF12-04 ④		Rc1/2	13	42.5	32			30.7	24		50	PLF12-04_
PLF5/32-M5 ④	5/32	M5 × 0.8	5	19	14	10	14.9	18.7	10	2.8	6.9	PLF5/32-M5_
PLF5/32-01 ④		Rc1/8	7	25	20				14		14	PLF5/32-01_
PLF5/32-02 ④		Rc1/4	9.5	31	26			20.7	17		21	PLF5/32-02_
PLF3/16-M5 ④	3/16	M5 × 0.8	5	20.8	14.5	12.5	17.4	20.7	10	3.3	8	PLF3/16-M5_
PLF3/16-01 ④		Rc1/8	7	26.8	20.5				14		15	PLF3/16-01_
PLF3/16-02 ④		Rc1/4	9.5	31.3	25			22.2	17		22	PLF3/16-02_
PLF1/4-M5 ④	1/4	M5 × 0.8	5	20.8	14.5	12.5	17	20.3	10	4.1	7.7	PLF1/4-M5_
PLF1/4-01 ④		Rc1/8	7	26.8	20.5				14		15	PLF1/4-01_
PLF1/4-02 ④		Rc1/4	9.5	31.3	25			21.8	17	5.3	21	PLF1/4-02_
PLF1/4-03 ④		Rc3/8	10.5	33.8	27.5			23.8	21		31	PLF1/4-03_
PLF5/16-01 ④	5/16	Rc1/8	7	28.3	21	14.5	18.1	22.7	14	6.7	16	PLF5/16-01_
PLF5/16-02 ④		Rc1/4	9.5	32.3	25			23.7	17		23	PLF5/16-02_
PLF5/16-03 ④		Rc3/8	10.5	34.3	27			24.7	21		33	PLF5/16-03_
PLF3/8-02 ④	3/8	Rc1/4	9.5	34.3	25.5	17.5	20.2	26	17	8.2	26	PLF3/8-02_
PLF3/8-03 ④		Rc3/8	10.5	36.8	28			27	21		36	PLF3/8-03_
PLF3/8-04 ④		Rc1/2	13	40.3	31.5			27.5	24		46	PLF3/8-04_
PLF1/2-02 ④	1/2	Rc1/4	9.5	38	27.5	21	23.7	30	17	10.0	31	PLF1/2-02_
PLF1/2-03 ④		Rc3/8	10.5	39	28.5				21		39	PLF1/2-03_
PLF1/2-04 ④		Rc1/2	13	42.5	32			31	24		54	PLF1/2-04_

※ 1. ④ in Model code / Replaced with "W" for Light-gray color, "-C" for Clean-room package, "W-C" for Light-gray color and Clean-room package, "-UC" for Clean-wash and Clean-room package

※ 2. Orifice bore is the smallest passage converted in terms of the diameter.