




PLL Long Elbow

RoHS compliant



Metric thread type



ø16mm type

OP.
P.754

3D
CAD

CAD

Unit : mm

Model code	Tube O.D. øD	R	A	B	L	øP	Tube end C	E	Hex. H	Orifice bore (ømm)	Weight (g)	CAD file name
PLL4-M5 ④	4	M5×0.8	2.8 [3]	28	30.2 [30]	10	14.9	18.7	8	2.4	6.4	PLL4-M5_[C]
PLL4-01 ④		R1/8	8	34	35			20.7	10	2.8	11	PLL4-01_
PLL4-02 ④		R1/4	11	41	40				14		19	PLL4-02_
PLL6-M5 ④	6	M5×0.8	2.8 [3]	34	37.5 [37.3]	12.5	17	20.3	10	2.4	9.9	PLL6-M5_[C]
PLL6-01 ④		R1/8	8	37	39.3			21.8	14	4.3	13	PLL6-01_
PLL6-02 ④		R1/4	11	42.5	42.7						20	PLL6-02_
PLL6-03 ④		R3/8	12	46	45.9			23.8	17		33	PLL6-03_
PLL8-01 ④	8	R1/8	8	40.5	43.8	14.5	18.1	22.7	12	6.7	16	PLL8-01_
PLL8-02 ④		R1/4	11	44.5	45.7			23.7	14		22	PLL8-02_
PLL8-03 ④		R3/8	12	47.5	48.4			24.7	17		35	PLL8-03_
PLL10-01 ④	10	R1/8	8	44.5	49.3	17.5	20.2	25.5	12	6	20	PLL10-01_
PLL10-02 ④		R1/4	11	48	50.7			26	14	8	26	PLL10-02_
PLL10-03 ④		R3/8	12	51.5	53.9			27	17	8.3	38	PLL10-03_
PLL10-04 ④		R1/2	15	55.5	56.1				21		63	PLL10-04_
PLL12-02 ④	12	R1/4	11	52.8	57.2	21	23.4	29	14	8	30	PLL12-02_
PLL12-03 ④		R3/8	12	55.5	59.7			29.7	17	10	42	PLL12-03_
PLL12-04 ④		R1/2	15	59.5	61.8				21	10.3	68	PLL12-04_
PLL16-03 ④	16	R3/8	11	74	80.2	25	24.1	33.1	22	11	154	PLL16-03_
PLL16-04 ④		R1/2	15	78	82.3					13	150	PLL16-04_
PLL5/32-01 ④	5/32	R1/8	8	34	35	10	14.9	18.7	10	2.8	11	PLL5_32-01_
PLL5/32-02 ④		R1/4	11	41	40			20.7	14		19	PLL5_32-02_
PLL3/16-01 ④	3/16	R1/8	8	37	39.3	12.5	17.4	20.7	10	3.3	13	PLL3_16-01_
PLL3/16-02 ④		R1/4	11	42.5	42.7			22.2	14		21	PLL3_16-02_
PLL1/4-01 ④	1/4	R1/8	8	37	39.3	12.5	17	20.3	10	4.6	13	PLL1_4-01_
PLL1/4-02 ④		R1/4	11	42.5	42.7			21.8	14		20	PLL1_4-02_
PLL1/4-03 ④		R3/8	12	46	45.9			23.8	17	5.3	33	PLL1_4-03_
PLL5/16-01 ④	5/16	R1/8	8	40.5	43.8	14.5	18.1	22.7	12	6	16	PLL5_16-01_
PLL5/16-02 ④		R1/4	11	44.5	45.7			23.7	14		22	PLL5_16-02_
PLL5/16-03 ④		R3/8	12	47.5	48.4			24.7	17	6.7	35	PLL5_16-03_
PLL3/8-01 ④	3/8	R1/8	8	44.5	49.3	17.5	20.2	25.5	12	6	20	PLL3_8-01_
PLL3/8-02 ④		R1/4	11	48	50.7			26	14	8	27	PLL3_8-02_
PLL3/8-03 ④		R3/8	12	51.5	53.9			27	17	8.2	39	PLL3_8-03_
PLL3/8-04 ④		R1/2	15	55.5	56.1				21		63	PLL3_8-04_
PLL1/2-02 ④	1/2	R1/4	11	52.8	57.2	21	23.7	29.3	14	8	30	PLL1_2-02_
PLL1/2-03 ④		R3/8	12	55.5	59.7			30	17	10	42	PLL1_2-03_
PLL1/2-04 ④		R1/2	15	59.5	61.8				21	10.9	67	PLL1_2-04_

※ 1. ④ in Model code / Replaced with "W" for Light-gray color, "-C" for Clean-room package, "W-C" for Light-gray color and Clean-room package, "-UC" for Clean-wash and Clean-room package

※ 2. "L" is a reference value for height dimension after tightening taper thread.

※ 3. Dimensions in [] are for clean-room and clean-wash package products

※ 4. Orifice bore is the smallest passage converted in terms of the diameter.