


Fitting Series

Tube Fitting

PU Union Straight

RoHS compliant




OP P.754 3D CAD

Unit : mm

Model code	Tube O.D. øD	B	øP	Tube end C	Orifice bore (ømm)	Weight (g)	CAD file name
PU4④	4	30.8	10	14.9	2.8	4.7	PU4
PU6④	6	34.9	12.5	17	4.3	6.5	PU6
PU8④	8	37.8	14.5	18.1	7	9.4	PU8
PU10④	10	41.4	17.5	20.2	9	16	PU10
PU12④	12	47.8	21	23.4	11	22	PU12
PU16④	16	49.4	25	24.1	13	26	PU16
PU5/32④	5/32	30.8	10	14.9	2.8	4.7	PU5_32
PU3/16④	3/16	35.7	12.5	17.4	3.3	6.7	PU3_16
PU1/4④	1/4	34.9	12.5	17	5	6.4	PU1_4
PU5/16④	5/16	37.8	14.5	18.1	7	9.4	PU5_16
PU3/8④	3/8	41.4	17.5	20.2	9	16	PU3_8
PU1/2④	1/2	48.4	21	23.7	11	21	PU1_2
PU5/8④	5/8	49.4	25	24.1	13	26	PU5_8

PG Unequal Union Straight

RoHS compliant



OP P.754 3D CAD

Unit : mm

Model code	Tube O.D. øD1	Tube O.D. øD2	B	øP1	øP2	Tube end C1	Tube end C2	Orifice bore (ømm)	Weight (g)	CAD file name
PG6-4④	6	4	34.4	12.5	12.5	17	14.9	2.8	6.4	PG6-4
PG8-4④	8	4	36.6	14.5	10.7	18.1	14.9	2.8	7.2	PG8-4
PG8-6④	8	6	37.9	14.5	14.5	17	17	4.3	8.8	PG8-6
PG10-6④	10	6	39.8	17.5	13	20.2	17	4.3	12	PG10-6
PG10-8④	10	8	41.1	17.5	17.5	18.1	18.1	6.5	14	PG10-8
PG12-8④	12	8	44	21	14.5	18.1	18.1	6.2	16	PG12-8
PG12-10④	12	10	47.6	21	21	23.4	20.2	9	21	PG12-10
PG12-3/8④	12	3/8	47.6	21	21	23.4	20.2	9	21	PG12-3_8
PG16-10④	16	10	52.1	25	25	24.1	20.7	8.4	35	PG16-10
PG16-12④	16	12	49.5	25	25	24.1	23.4	10	27	PG16-12
PG3/16-5/32④	3/16	5/32	34.8	12.5	12.5	17.4	14.9	2.8	6.4	PG3_16-5_32
PG1/4-5/32④	1/4	5/32	34.4	12.5	12.5	17	14.9	2.8	6.3	PG1_4-5_32
PG1/4-4④	1/4	4	35.3	12.5	12.5	17	17.4	3.3	6.5	PG1_4-3_16
PG1/4-3/16④	1/4	3/16	38.3	14.5	14.5	18.1	17.4	3.3	8.8	PG5_16-3_16
PG5/16-3/16④	5/16	3/16	37.9	14.5	14.5	18.1	17	5	8.7	PG5_16-1_4
PG5/16-1/4④	5/16	1/4	39.8	17.5	13	20.2	17	4.3	12	PG3_8-1_4
PG3/8-1/4④	3/8	1/4	41.1	17.5	17.5	20.2	18.1	6.5	15	PG3_8-5_16
PG3/8-5/16④	3/8	5/16	44.4	21	14.5	23.7	17	4.3	15	PG1_2-1_4
PG1/2-1/4④	1/2	1/4	44.3	21	14.5	23.7	18.1	6.2	16	PG1_2-5_16
PG1/2-5/16④	1/2	5/16	47.9	21	21	23.7	20.2	9	21	PG1_2-3_8
PG1/2-3/8④	1/2	3/8	49.8	25	25	24.1	23.7	10.7	26	PG5_8-1_2
PG5/8-1/2④	5/8	1/2	49.8	25	25	24.1	23.7	10.7	26	PG5_8-1_2

Common caution in this page

※ 1. ④ in Model code / Replaced with "W" for Light-gray color, "-C" for Clean-room package, "W-C" for Light-gray color and Clean-room package, "-UC" for Clean-wash and Clean-room package

※ 2. Orifice bore is the smallest passage converted in terms of the diameter.

OP P.600

Page for special specifications

3D CAD

3D CAD data is available at PISCO website.

CAD

CAD data is available at PISCO website.