





Cross C

RoHS compliant



Release-ring dimension



Unit : mm

Model code	Tube O.D. øD1	Tube O.D. øD2	B	E1	E2	øP	Tube end C	F1	F2	T	D1 release-ring		D2 release-ring		Effective area (mm ²)	Weight (g)	CAD file name
											X	Y	X	Y			
PZC4-3M④⑤	4	3	26.1	13.05	13.05	8	11	11.2	5.6	8	9.8	7.8	9.8	7.8	2.2	4.4	PZC4-3M
PZC4-1/8M④⑤		1/8													2.4		PZC4-1/8M
PZC6-4M④⑤	6	4	29.5	14.55	14.95	10.5	11.6	13.2	6.6	10.5	11.8	9.8	9.8	7.8	4.9	6.3	PZC6-4M
PZC6-1/8M④⑤		1/8													2.4		PZC6-1/8M
PZC1/8-3M④⑤	1/8	3	26.1	13.05	13.05	8	11	11.2	5.6	8	9.8	7.8	9.8	7.8	1.9	4.5	PZC1/8-3M
PZC5/32-1/8M④⑤	5/32	1/8	26.1	13.05	13.05	8	11	11.2	5.6	8	9.8	7.8	9.8	7.8	2.2	4.4	PZC5/32-1/8M


※ 1. ④ in Model code / Replaced with "W" for Light-gray color

※ 2. ⑤ in Model code / Replaced with "C" for Clean-room package




Bulkhead Union

RoHS compliant



Release-ring dimension



Unit : mm

Model code	Tube O.D. øD	M	B	E	A	øP	Tube end C	Hex. H	G	X (øX)	Y	Effective area (mm ²)	Weight (g)	CAD file name
PM3M④⑤	3	M8×0.75	19.5	4.8	12.4	7	9.4	10	2	7	6	2.4	3.1	PM3M
PM4M④⑤	4	M10×1	23.2	5.8	14.1	8.9	10.9	12	3	7.8	—	3.7	6	PM4M
PM6M④⑤	6	M12×1	25	6.6	14.8	10.8	11.7	14	4	9.8	—	10.5	9	PM6M
PM1/8M④⑤	1/8	M10×1	23.2	5.8	14.1	8.9	10.9	12	3	7.8	—	2.1	6.1	PM1/8M
PM5/32M④⑤	5/32	M10×1	23.2	5.8	14.1	8.9	10.9	12	3	7.8	—	3.7	6	PM5/32M
PM1/4M④⑤	1/4	M12×1	24.6	6.4	14.8	10.8	11.4	14	4	9.8	—	11.2	8.8	PM1/4M

※ 1. ④ in Model code / Replaced with "W" for Light-gray color

※ 2. ⑤ in Model code / Replaced with "C" for Clean-room package